

# GAMMA PEARL 1024B



512/1990 STANDARD, MAXIMUM 1024 CONTROL CHANNELS, PHOTOELECTRIC ISOLATION SIGNAL OUTPUT

L CONTROL 96 LARGEST AMOUNT OF DIMMING OR 96 ROAD, USE PEARL LAMP BASE.

L BUILT-IN GRAPHICS TRAJECTORY GENERATOR, THERE ARE 135 BUILT-IN GRAPHICS, CONVENIENT FOR USER TO GRAPHICS TRAJECTORY CONTROL OF AMOUNT, PICTURESQUE, SPIRAL, RAINBOW, CHASING, AND OTHER EFFECTS.

GRAPHIC PARAMETERS (E.G. AMPLITUDE, SPEED, INTERVAL, WAVE, DIRECTION) CAN BE

SET INDEPENDENTLY. LI CONSOLE HAS THE FUNCTION OF WRITING LAMP LIBRARY. L 60 REPEAT SCENARIO, A

MULTI-STEP SCENARIO IS USED TO STORE AND SINGLE-STEP SCENARIO. A MULTI-STEP SCENARIO CAN STORE UP TO 600 STEPS

L WITH BACKLIT LCD DISPLAY, I SHUTDOWN DATA MAINTAIN IN BOTH CHINESE AND ENGLISH. LU

DISL BACKUPS AND UPGRADES. L WORK PROFESSIONAL GOOSENECK LAMP, SUITABLE FOR INDOOR AND OUTDOOR

PERFORMANCES. (OPTIONAL) L POWER SUPPLY: AC 100-240V / 50 TO 60 HZ

